

SUNCOM 新创电源	产品类型	LED 驱动电源 LED INTEGRATED SPECIAL DRIVER		
	产品系列	HVC-240W-343X系列	REV	V3.0

广东新创电源科技有限公司

客户承认书

SPECIFICATION FOR APPROVAL

CUSTOMER/客户名:	
MODEL NO. /产品型号:	HVC-240W-343X系列
Rev. /版本号	V3.0
SAMPLE DATE/送样日期:	

客户确认栏

TESTED BY 检查	CHECKED BY 审核	APPROVED BY 批准
客户备注		

Please return to us one copy of “SPECIFICATION FOR APPROVAL” with you approved signature. /客户确认签章后请回传一份承认书给我公司.

新创确认栏

TESTED BY 检查	CHECKED BY 审核	APPROVED BY 批准

Guangdong Suncom Power Technology Co., Ltd

广东新创电源科技有限公司

No.1 of Yongyi 3rd Road Henglan Town Zhongshan Guangdong China Post code528478

地址：广东省中山市横栏镇永兴工业区永谊三路1号 邮编：528478

TEL:0760-22326609 28168136 FAX:0760-87600929

日期	变更原因	版本	批准
DATA	CAUSES OF CHANGE	REV.	APPROVED

[illegible]

SUNCOM 新创电源	产品类型	LED 驱动电源 LED INTEGRATED SPECIAL DRIVER		
	产品系列	HVC-240W-343X系列	REV	V3.0

◆ Features 产品特性:

- Input Rated voltage : 100-277Vac 50Hz/60Hz
输入额定电压范围:100-277Vac 50Hz/60Hz
- Isolation, constant current mode output
隔离, 恒流模式输出
- Surge Protection: L-N :6KV; L/N- E:10KV
防雷保护: 火线对零线6KV, 火线/零线对地10KV
- 3 in 1 dimming(dim-to-off)
三合一调光 (调光可关断, 隔离设计)
- Over temperature drop current
过温降电流
- Output current is adjustable
输出电流可调
- THD<10%

◆ Applications 产品应用:

Application: Street light、high bay lighting and other lighting lamps
应用于: 路灯、工矿灯等照明灯具

◆ Description 产品描述:

This product is a constant current Power Supply, Specially designed for LED, With low harmonic (< 10%), High Power Factor. Flicker free, Output current can be flexibly adjusted according to LED lamp voltage. 3 in 1 Dimming function.Built-in Surge Protection, Output Open-Circuit Protection, Short-Circuit Protection, Over Temperature drop current protection. Greatly improve the safety and reliability of the product.

本产品为恒流驱动电源, 专为LED设计, 具有低谐波 (<10%)、高功率因数、无频闪, 输出电流可根据LED灯电压灵活调节。三合一调光功能。内置防雷保护, 输出开路、短路保护, 过温降电流保护, 极大的提高了产品的安全可靠。

	产品类型	LED 驱动电源 LED INTEGRATED SPECIAL DRIVER		
	产品系列	HVC-240W-343X系列	REV	V3.0

■ MODEL LIST 型号列表

Model 型号	Rated Power 额定输出功率	Input Voltage 输入电压	Output Voltage 输出电压范围	Output Current 输出电流	THD. (Typ)	PF. (Typ)
HVC-240W-343X	240W	100-277Vac	171-343V	0.5A-1.05A	7.8%	0.95

NOTE: All parameters NOT special mentioned are measured at 230Vac input,rated load and 25℃ of ambient temperature ; 如未特殊注明，所有参数均在 230Vac 输入、额定负载、25℃环境温度下测量

■ “X” Means Additional Function 后缀 “X” 功能可选机型表

“X”	ADJ Current (可调电流：后缀A)	0-10V/PWM Dim/Resistor (三合一调光：后缀B)	0-10V/PWM Dim/Resistor +AUX 12V (三合一调光+辅组源：后缀C)
B		√	

■ ELECTRICAL SPECIFICATION 电气规格

◆ 输入性能 Input performance:

Parameter 参数	Min. 最小值	Typ. 典型值	Max. 最大值	Notes. 备注
Voltage Range 电压范围	100Vac	120-277Vac	305ac	-
Frequency Range 频率范围	47Hz	50/60Hz	63Hz	-
AC Current 交流电流	-	-	3.0A	At 120V AC input,full load 满载，输入120Vac
Inrush Current 浪涌电流	-	-	60A	At 230Vac input,25℃ cold start 环温 25℃，230Vac 冷机启动
PF. 功率因数 At 230V AC input,full load 满载，输入 230Vac 下测量	0.95	0.97	-	-
THD. 总谐波失真 At 230V AC input,full load 满载，输入 230Vac 下测量	-	7.8%	10%	-
No Load Power 空载待机功耗	-	-	0.5W	At 220Vac input, Dim-to-Off with Standby; 输入 220V 条件下，将调光信号调到关闭后进入待机状态 (仅 C 版本)

◆ 输出性能：Output performance

Parameter 参数	Min. 最小值	Typ. 典型值	Max. 最大值	Notes. 备注
Voltage Range 电压范围	171VDC	-	343VDC	
Current range Regulation 电流调节范围(电位器)	0.5A	-	1.05A	

SUNCOM 新创电源		产品类型	LED 驱动电源 LED INTEGRATED SPECIAL DRIVER		
		产品系列	HVC-240W-343X系列	REV	V3.0
Rated Power 额定功率 (120-277Vac)	-	-	240W	-	
Output Power 输出功率 (90-100Vac)	-	120W	240W	The derating begins when the input voltage is less than 100Vac 输入电压小于 100Vac时开始降额	
No Load Output Voltage 输出空载电压	-	-	385V	-	
Efficiency 效率 Measured at full load and	91%	94%	-	At 230V AC input, 343VDC Output full load; 输出343VDC 满载, 输入230V条件下	
Current Tolerance 电流精度	-5%	-	+5%	-	
Line Regulation 线性调整率	-3%	-	+3%	-	
Load Regulation 负载调整率	-3%	-	+3%	-	
Current Ripple 纹波电流		-	<±5%	-	
Turn-on Delay Time 启动时间	300mS	-	<1S	Measured at full load and 120-277Vac input; 输入 120-277Vac, 满载条件下	
Short Circuit Protection 短路保护	-	-	15W	Hiccup mode, recovers automatically after fault condition is removed 打嗝模式, 故障排除后自动恢复	
Over-temperature protection过温保护	-	90℃	-	Shell Tc point temperature, Drop current mode, the current automatically recovers after over temperature release, 外壳TC点温度, 降电流模式, 过温解除后, 电流自动恢复	

■ 环境：Environment

Parameter 参数	Min. 最小值	Typ. 典型值	Max. 最大值	Notes. 备注
Working TEMP 工作温度	-40℃	+25℃	+60℃	-
Storage TEMP 储存温度	-40℃	+25℃	+85℃	-
Working Humidity 工作湿度	20% RH	-	90% RH	-
Storage Humidity 储存湿度	10% RH	-	90% RH	-
Maximum shell TEMP 最大壳温	-	-	+90℃	-

■ 安规和电磁兼容：

Withstand voltage 耐压	I/P - FG:1.75KVAC, I/P-O/P:3.75KVAC, I/P-调光: 3.75KVAC, O/P-调光: 1.5KVAC		
Isolation Resistance 绝缘阻抗	100MΩ at I/P - FG 500VDC; I/P-O/P:100MΩ at 500VDC / 25℃		
leakage Current 漏电流	<0.7mA/277Vac		
Earthing Resistance 接地电阻	<0.1Ω / 25A 1 min		
Surge 浪涌	差模 L-N +/- 6KV (2 ohm), 共模 L, N-E +/- 10KV (12 ohm)		
Conducted electromagnetic interference 传导	>3dB		
Radiated electromagnetic interference 辐射	>3dB		

NOTE:

- 1) All parameters NOT specially mentioned are measured at 230Vac (50Hz) input, rated load and 25℃ of ambient temperature.
如未特别说明, 所有规格参数均在 230Vac (50Hz) 输入, 额定负载, 环境温度 25℃ 的条件下进行测量
- 2) Tolerance : includes set up tolerance, line regulation and load regulation.

误差：包含设定误差、线性调整率和负载调整率。


SUNCOM 新创电源	产品类型	LED 驱动电源 LED INTEGRATED SPECIAL DRIVER		
	产品系列	HVC-240W-343X系列	REV	V3.0

THD VS INPUT VOLTAGE

THD VS输入电压

PF VS INPUT VOLTAGE

PF 值 VS 输入电压




INPUT VOLTAGE VS LOADING

输入 电压 VS 输出负载

LOAD DERATING CURVE

降额曲线




EFFICIENCY VS INPUT VOLTAGE

效率 VS 输入电压

TCASE VS LIFETIME

壳温VS寿命



THE DIMMING CURVE 调光曲线

三合一调光功能及12V辅助源输出：

．在DIM+（紫色线）和DIM-（灰色线）间连接一个电阻或0-10V直流电压或PWM信号，即可调整输出恒电流的数值；



．调光端口输出电流：100uA（典型值）

．辅助源:12V/250mA(粉色线)

三合一调光曲线



0-10V调光

用外加0-10VDC电压





PWM调光（PWM频率 1KHZ）

用外加 PWM信号（频率0.5K-5K）



电阻调光（100K）

用外加电阻（0-100K）




MECHANICAL SPECIFICATION & PACKING 机械尺寸图 & 包装:

Bare plate dimension 裸板尺寸	189.3*56*30mm (L*W*H)
final dimension 成品尺寸	224.5*69*36.2mm (L*W*H)
Product Weight 产品重量	1092g


Case No. 机壳型号: 240W

Unit 单位:mm


HVC-240W-343A



HVC-240W-343B



HVC-240W-343C



SUNCOM 新创电源	产品类型	LED 驱动电源 LED INTEGRATED SPECIAL DRIVER		
	产品系列	HVC-240W-343X系列	REV	V3.0

Nameplate 铭牌

尺寸:196.5*48mm 样式: 贴纸

HVC-240W-343A SUNCOM HVC-240W-343A (型号)LED控制装置 <table><tr><td>INPUT 输入端</td><td>Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95</td><td>Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W</td><td>OUTPUT 输出端</td></tr><tr><td>○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)</td><td>•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China</td><td>ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~</td><td>(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○</td></tr></table> 广东新创电源科技有限公司 GUANGDONG SUNCOM POWER TECHNOLOGY CO., LTD CE CB IP67	INPUT 输入端	Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95	Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W	OUTPUT 输出端	○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)	•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China	ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~	(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○	HVC-240W-343B SUNCOM HVC-240W-343B (型号)LED控制装置 <table><tr><td>INPUT 输入端</td><td>Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95</td><td>Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W</td><td>OUTPUT 输出端</td></tr><tr><td>○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)</td><td>•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China</td><td>ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~</td><td>(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○ (VT黄)DIM + ○ (PK粉)DIM - ○</td></tr></table> 广东新创电源科技有限公司 GUANGDONG SUNCOM POWER TECHNOLOGY CO., LTD CE CB IP67	INPUT 输入端	Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95	Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W	OUTPUT 输出端	○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)	•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China	ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~	(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○ (VT黄)DIM + ○ (PK粉)DIM - ○
INPUT 输入端	Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95	Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W	OUTPUT 输出端														
○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)	•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China	ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~	(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○														
INPUT 输入端	Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95	Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W	OUTPUT 输出端														
○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)	•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China	ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~	(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○ (VT黄)DIM + ○ (PK粉)DIM - ○														
HVC-240W-343C SUNCOM HVC-240W-343C (型号)LED控制装置 <table><tr><td>INPUT 输入端</td><td>Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95</td><td>Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W</td><td>OUTPUT 输出端</td></tr><tr><td>○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)</td><td>•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China</td><td>ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~</td><td>(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○ (VT黄)DIM + ○ (BK黑/WH白)12V -/DIM - ○ (PK粉)12V + ○</td></tr></table> 广东新创电源科技有限公司 GUANGDONG SUNCOM POWER TECHNOLOGY CO., LTD CE CB IP67	INPUT 输入端	Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95	Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W	OUTPUT 输出端	○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)	•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China	ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~	(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○ (VT黄)DIM + ○ (BK黑/WH白)12V -/DIM - ○ (PK粉)12V + ○									
INPUT 输入端	Vin(输入):100-240V~3A 50/60Hz Vin(输入):277V~1.1A 50/60Hz η:≥93% PF:≥0.95	Vout(输出):171-343V = 500-1050mA Max.(最大电压):Uout 380V = Rated Power(额定功率):240W	OUTPUT 输出端														
○ ACL-(BN棕)BK-黑 ○ ACN-(BU蓝)WH-白 ⊕ (GN绿/YL黄)	•tc *277 for North American only. Suitable for dry,Damp and wet locations No. 1-02, Yongyi Road Three, Yongqing Industry Zone, Henglan Town, Zhongshan City, 528478 Guangdong, China	ta:50°C@Vin100-200V~ ta:60°C@Vin200-277V~	(BN棕)RD-红 Vo + ○ (BU蓝)BK-黑 Vo - ○ (VT黄)DIM + ○ (BK黑/WH白)12V -/DIM - ○ (PK粉)12V + ○														